

HAYMES ARTISAN COLLECTION

Soft Chalk

Product Code: ACSC

Product description

Haymes Artisan Collection Soft Chalk is a multi-faceted product with the added qualities of superior adhesion and sandability, perfect for both broadwall applications and furniture pieces. This product has a deep velvety finish that is also soft and chalky in appearance and gives a bespoke look. This rich matt finish shows the marks of the application of the roller as subtle undulating movement within the finish adding to its sense of depth.



Key Features

- ✓ Bespoke Texture
- ✓ Handcrafted finish
- ✓ Premium Quality
- ✓ Interior

Where to Use

Interior broad wall applications such as; ceilings, walls, furniture, and other interior surfaces.

Not recommended for high traffic areas, bathrooms or wet areas.

Note: If marking of the coating is visible this can be simply refreshed by application of another coat. If you are seeking washability and mark resistance we recommend our Expressions Interior Acrylic range.

Typical properties

Gloss	Matt <5
Application tools	Brush, synthetic roller
Clean-up	Water
Dry time	Touch dry 20 mins Recoat 2 hours
Coverage	Up to 16m ² /L and is dependent upon application technique.
Colour	White, EDT
Sizes	500ml, 1L, 4L
VOC	44 g/L
Volume solids	40%
Film build	Wet 83 µm Dry 33 µm

Surface Preparation

General Surface Preparation	<ol style="list-style-type: none">1. Fill cracks, nail holes and imperfections with Haymes Unifill.2. Wash surface with Haymes Unikleen and rinse with clean water.3. Scrape all loose/flaking paint. Sand smooth & dust down.4. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.5. Prime bare plaster, timber and metal areas with appropriate Haymes undercoats or primers.
Previously Painted Surfaces	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Apply one coat of Haymes Ultraseal to any patched areas.3. Sand gloss surfaces to a dull finish. Remove all dust4. For surfaces in good condition no primers or undercoats are required.
Plasterboard	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Apply one coat of Haymes Ultraseal

Application

Do NOT apply if ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period.

1. Stir thoroughly before and during application using a broad flat stirrer.
2. Apply 2 coats with a synthetic medium nap roller or by brush using criss-cross method to achieve your desired finish.
3. Allow to dry for two hours between coats.
4. When using darker toned colours the unique application marks may be more visible.

All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.

IMPORTANT NOTE: The finished result of decorative finishes will vary dependent upon the applicator and the application technique used. Haymes Paint recommend a sample application be conducted prior to undertaking your project to ensure satisfaction with the outcome. This is due to the variance that may be experienced between the Haymes finished sample and that achieved by the applicator. We recommend viewing our instructional videos located at www.haymespaint.com.au/artisancollection

Thinning

When brushing product may be thinned with up to 50ml of clean water per litre of paint. On very porous surfaces add up to 100ml clean water per litre of paint.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Date of Preparation 24/10/2017